MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name IdeaPaint CREATE part A (THAT)

Version # 03 **Revision date** 12-13-11 CAS# Mixture

Product code CREATE (A) (THAT) Product use Dry erase coating.

Manufacturer/Supplier IdeaPaint

Address 290 Eliot Street, 2nd Floor, Ashland, MA 01721

Telephone number 617.714.1050 E-mail Not available. **Contact person** Not available. 24-HourEmergency: 866-519-4752

3E, US Contract: 12654, Access Code: 333641

2. Hazards Identification

Liquid. Physical state

Appearance Opaque liquid. **Emergency overview** WARNING

> May be harmful if swallowed. Irritating to eyes and skin. May cause allergic skin reaction. This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

OSHA regulatory status

Potential health effects

Routes of exposure

Inhalation. Ingestion. Skin contact. Eye contact.

Eyes Irritating to eyes. Skin Irritating to skin.

Inhalation Prolonged inhalation may be harmful.

Ingestion Harmful if swallowed. Irritating to mouth, throat, and stomach.

Target organs Eyes. Skin.

Chronic effects Preparation contains an epoxy resin, which may cause sensitization and development of allergy.

Skin irritation. Irritation of eyes and mucous membranes. Sensitization. Signs and symptoms

Potential environmental effects Toxic to aquatic organisms. May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Titanium Dioxide	13463-67-7	15-40
Aluminium oxide	1344-28-1	0.5-1.5
Silicon dioxide	7631-86-9	0.5-1.5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses

and open eyes wide apart. Get medical attention if irritation develops or persists.

Skin contact Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. Get

medical attention if irritation develops or persists.

CPH MSDS US IdeaPaint CREATE part A (THAT)

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

Treat symptomatically.

General advice

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire Fighting Measures

Flammable properties

The product is not flammable.

Extinguishing media

Suitable extinguishing

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Unsuitable extinguishing

media

media

None known.

Protection of firefighters

Specific hazards arising from the chemical

Fire or high temperatures create: Carbon oxides. Nitrogen oxides. Metal oxides.

Protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this MSDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods for cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. This material and its container must be disposed of as hazardous waste.

Other information

Clean up in accordance with all applicable regulations. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. Handling and Storage

Handling

Use Personal Protective Equipment recommended in section 8 of the MSDS. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Persons with epoxy allergy should not work with this product. Avoid inhalation of vapors and contact with skin, eyes and clothing. Avoid release to the environment. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not reuse this container. "Empty" containers retain product residue (liquid or vapor) and can be dangerous.

IdeaPaint CREATE part A (THAT)

Store in accordance with local, regional, national, and international regulations. Store in tightly closed original container in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from incompatible materials. Keep away from food, drink and animal feeding stuffs. Do not store in unlabelled containers. Keep container tightly closed in a dry and well-ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate container to avoid environmental contamination. Store at temperature below 49°C.

6 ma/m3

5 ma/m3

15 mg/m3

Unspecified.

Respirable fraction.

Total dust.

8. Exposure Controls / Personal Protection

Occupational exposure limits

Silicon dioxide (7631-86-9)

Components	Туре	Value	Form
Aluminium oxide (1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Silicon dioxide (7631-86-9)	TWA	3 mg/m3 10 mg/m3	Respirable particles. Inhalable particles.
Titanium Dioxide (13463-67-7)	TWA	10 mg/m3	·
U.S OSHA	-	W.L.	-
Components	Туре	Value	Form

		20 mppcf	Unspecified.	
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)				
Components	Туре	Value	Form	
Aluminium oxide (1344-28-1)	PEL	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
Silicon dioxide (7631-86-9)	PEL	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
Titanium Dioxide (13463-67-7)	PEL	15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 CFR 1910	.1000)			
Components	[^] Type	Value	Form	

TWA

TWA

Engineering controlsEnsure adequate ventilation, especially in confined areas. Provide easy access to water supply and eye wash facilities.

Personal protective equipment

Silicon dioxide (7631-86-9)

Eye / face protection Chemical goggles are recommended.

Skin protection Wear protective gloves. Butyl rubber gloves are recommended. Wear suitable protective clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a properly fitted, particulate filter respirator complying with an approved

standard if a risk assessment indicates this is necessary.

General hygieneAlways observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove

contaminants. Discard contaminated footwear that cannot be cleaned. Do not eat, drink or smoke when using the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance Opaque liquid.

Color White.

Odor Not available.

Odor threshold Not available.

Physical state Liquid.
Form Liquid.

pH Not available.Melting point Not available.Freezing point Not available.

Boiling point $> 100 \, ^{\circ}\text{F} \, (> 37.8 \, ^{\circ}\text{C})$

IdeaPaint CREATE part A (THAT)
904458 Version #: 03 Revision date: 12-13-2011 Print date: 12-13-2011

Flash point 207 °F (97.2 °C) Closed Cup

Evaporation rate 69 BuAc **Flammability limits in air, upper,** Not available.

% by volume

Flammability limits in air, lower, Not available.

% by volume

Vapor pressure1.5 kPa (20 °C)Vapor densityNot available.Specific gravityNot available.Solubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

VOC < 25 q/l

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions.

Conditions to avoid Heat.

Incompatible materials Water. Acids. Oxidizing material. Strong alkaline.

Hazardous decomposition

products

None in particular.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

11. Toxicological Information

Toxicological data

Components Test Results

Silicon dioxide (7631-86-9) Acute Oral LD50 Mouse: > 15000 mg/kg

Acute Oral LD50 Rat: > 22500 mg/kg

Acute effects Harmful if swallowed. Irritating to eyes and skin.

Local effects Irritating to eyes and skin.

Sensitization May cause sensitization by skin contact.

Chronic effects Preparation contains an epoxy resin, which may cause sensitization and development of allergy.

Carcinogenicity Hazardous by OSHA criteria. Hazardous by WHMIS criteria. Cancer hazard.

ACGIH Carcinogens

Aluminium oxide (CAS 1344-28-1)

A4 Not classifiable as a human carcinogen.

Titanium Dioxide (CAS 13463-67-7)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon dioxide (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Mutagenicity No data available.

Symptoms and target

organs

Skin irritation. Irritation of eyes and mucous membranes. Sensitization.

Further information No other specific acute or chronic health impact noted.

12. Ecological Information

Ecotoxicological data

Components Test Results

Titanium Dioxide (13463-67-7) EC50 Water flea (Daphnia magna): > 1000 mg/l 48 hours

LC50 Mummichog (Fundulus heteroclitus): > 1000 mg/l 96

hours

EcotoxicityToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CPH MSDS US

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulation /

Accumulation

Not available.

Mobility in environmental

media

Not available.

Partition coefficient (n-octanol/water)

Not available.

13. Disposal Considerations

Waste from residues / unused

products

Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all

applicable regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Basic shipping requirements:

UN number UN3082

Proper shipping name Environmentally hazardous substances, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)

sebacate)

Hazard class Packing group Environmental Ш

hazards

Marine pollutant Labels Yes required Additional 9

information:

Special provisions 8, 146, 335, IB3, T4, TP1, TP29

Packaging exceptions 155 Packaging non bulk 203 Packaging bulk 241

IATA

Basic shipping requirements:

UN number

Proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)

sebacate)

Hazard class Packing Ш group Environmental

hazards

Marine pollutant Yes

Additional information:

ERG code 9L

IMDG

Basic shipping requirements:

UN number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Proper shipping name

(Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)

Hazard class Packing Ш group Environmental

hazards

EmS No.

Marine pollutant

Yes F-A, S-F

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D)

Not regulated.

CPH MSDS US IdeaPaint CREATE part A (THAT)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Aluminium oxide (CAS 1344-28-1)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Aluminium oxide (CAS 1344-28-1) Listed.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Inventory name

Section 302 extremely hazardous substance (40 CRF 355, Appendix A)

Country(s) or region

United States & Puerto Rico

Section 311/312 (40 CFR

No

370)

Inventory status

Australia

/ tabti ana	radialian inventory of oriential eabetanees (rade)	100
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations WARNING: This product contains chemicals known to the State of California to cause cancer.

Australian Inventory of Chemical Substances (AICS)

US - California Hazardous Substances (Director's): Listed substance

Aluminium oxide (CAS 1344-28-1) Listed Silicon dioxide (CAS 7631-86-9) Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Listed: September 2, 2011 Carcinogenic. Titanium Dioxide (CAS 13463-67-7)

US - Massachusetts RTK - Substance: Listed substance

Aluminium oxide (CAS 1344-28-1) Listed. Silicon dioxide (CAS 7631-86-9) Listed. Titanium Dioxide (CAS 13463-67-7) Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Aluminium oxide (CAS 1344-28-1) 500 LBS

US - New Jersey RTK - Substances: Listed substance

Aluminium oxide (CAS 1344-28-1) Listed. Silicon dioxide (CAS 7631-86-9) Listed. Titanium Dioxide (CAS 13463-67-7) Listed. US - Pennsylvania RTK - Hazardous Substances: Listed substance

Aluminium oxide (CAS 1344-28-1) Listed. Silicon dioxide (CAS 7631-86-9) Listed. Titanium Dioxide (CAS 13463-67-7) Listed.

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

CPH MSDS US IdeaPaint CREATE part A (THAT)

On inventory (yes/no)*

Yes

Yes

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

NFPA ratings

Health: 1 Flammability: 1 Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently

available.

Issue date 10-05-2011

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name IdeaPaint CREATE part B (THIS)

Version # 03

Revision date 12-13-2011 CAS# Mixture

Product code CREATE (B) (THIS) **Product use** Dry erase coating.

Manufacturer/Supplier IdeaPaint

290 Eliot Street, 2nd Floor, Ashland, MA 01721 **Address**

Telephone number 617.714.1050 E-mail Not available. Not available. **Contact person** 24-HourEmergency: 866-519-4752

3E, US Contract: 12654, Access Code: 333641

2. Hazards Identification

Liquid. Physical state

Appearance Transparent liquid

Emergency overview WARNING

Irritating to eyes and skin.

OSHA regulatory status

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Eves Irritating to eyes. Skin Irritating to skin.

Inhalation Prolonged inhalation may be harmful. Ingestion Irritating to mouth, throat, and stomach.

Target organs Eyes. Respiratory system. Skin.

Chronic effects Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Signs and symptoms Skin irritation. Irritation of eyes and mucous membranes.

Potential environmental effects Toxic to aquatic organisms. May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Components	CAS#	Percent
n-[3-(Trimethoxysilyl)propyl]butylamine	31024-56-3	35-90
n-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	15-40
Dibutyltin dilaurate	77-58-7	0.5-<5.0

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses

and open eyes wide apart. Get medical attention if irritation develops or persists.

Skin contact Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. Get

medical attention if irritation develops or persists.

CPH MSDS US IdeaPaint CREATE part B (THIS)

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

Treat symptomatically.

General advice

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire Fighting Measures

Flammable properties

The product is not flammable.

Extinguishing media

Suitable extinguishing

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

media

Unsuitable extinguishing

media

None known.

Protection of firefighters

Specific hazards arising from the chemical

Fire or high temperatures create: Carbon oxides. Nitrogen oxides. Metal oxides.

Protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this MSDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods for cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. This material and its container must be disposed of as hazardous waste.

Other information

Clean up in accordance with all applicable regulations. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. Handling and Storage

Handling

Use Personal Protective Equipment recommended in section 8 of the MSDS. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Persons with epoxy allergy should not work with this product. Avoid inhalation of vapors and contact with skin, eyes and clothing. Avoid release to the environment. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not reuse this container. "Empty" containers retain product residue (liquid or vapor) and can be dangerous.

IdeaPaint CREATE part B (THIS)

Store in accordance with local, regional, national, and international regulations. Store in tightly closed original container in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from incompatible materials. Keep away from food, drink and animal feeding stuffs. Do not store in unlabelled containers. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate container to avoid environmental contamination. Store at temperature below 49°C.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US	ACGIH	Threshold	l imit	Values

Components	Туре	Value	
Dibutyltin dilaurate (77-58-7)	STEL	0.2 mg/m3	
(11 00 1)	TWA	0.1 mg/m3	
US. OSHA Table Z-1 Limits for	Air Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	
Dibutyltin dilaurate	PEL	0.1 mg/m3	
(77-58-7)			

Engineering controlsEnsure adequate ventilation, especially in confined areas. Provide easy access to water supply and eye wash facilities.

Personal protective equipment

Eye / face protection Chemical goggles are recommended.

Skin protection Wear protective gloves. Butyl rubber gloves are recommended. Wear suitable protective clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a properly fitted, particulate filter respirator complying with an approved

standard if a risk assessment indicates this is necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. Do not eat, drink or smoke when using the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance Transparent liquid

Color Clear.

OdorSlight ammonia.Odor thresholdNot available.

Physical state Liquid.
Form Liquid.

pH Not available.
 Melting point Not available.
 Freezing point Not available.
 Boiling point Not available.
 Flash point Not available.
 Evaporation rate Not available.

Flammability limits in air, upper, Not available.

% by volume

Flammability limits in air, lower, Not available.

% by volume

Vapor pressure Not available.

Vapor densityNot available.Specific gravityNot available.Solubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature Not available.

IdeaPaint CREATE part B (THIS)
904467 Version #: 03 Revision date: 12-13-2011 Print date: 12-13-2011

Not available. **Decomposition temperature** < 99 g/l VOC

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions.

Conditions to avoid Keep away from heat, sparks, and flame.

Incompatible materials Peroxides. Oxidizing agents. Acids. Alcohols. Reducing agents. Bases.

Hazardous decomposition

products

None expected under normal conditions of use.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

11. Toxicological Information

Acute effects Irritating to eyes and skin. Material generates methanol on contact with water or moisture in eye,

skin and mucous membranes and has an irritating dehydrating effect on overexposed tissue.

Local effects Harmful if swallowed. Components of the product may be absorbed into the body through the

skin. Contact may irritate or burn eyes. May cause sensitization by skin contact.

US ACGIH Threshold Limit Values: Skin designation

Dibutyltin dilaurate (CAS 77-58-7) Can be absorbed through the skin.

Sensitization May cause sensitization by skin contact.

Chronic effects Prolonged exposure may cause chronic effects.

No data available. Carcinogenicity

ACGIH Carcinogens

Dibutyltin dilaurate (CAS 77-58-7) A4 Not classifiable as a human carcinogen.

Mutagenicity No data available.

Symptoms and target

organs

Skin irritation. Irritation of eyes and mucous membranes.

12. Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **Ecotoxicity**

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulation /

Accumulation

Not available.

Mobility in environmental

media

Not available.

Partition coefficient

(n-octanol/water)

Not available.

13. Disposal Considerations

Waste from residues / unused

products

Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Basic shipping requirements:

UN number UN3082

Proper shipping name Environmentally hazardous substances, liquid, n.o.s. (Dibutyltin dilaurate)

Hazard class Packing 9 group Environmental

hazards

Ш

Marine pollutant Labels required Additional

Yes 9

information:

Special provisions 8, 146, 335, IB3, T4, TP1, TP29

CPH MSDS US IdeaPaint CREATE part B (THIS)

Packaging exceptions155Packaging non bulk203Packaging bulk241

IATA

Basic shipping requirements:

UN number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate)

Hazard class Packing 9 group Environmental III

hazards

Marine pollutant Yes

Additional information:

ERG code 9L

IMDG

Basic shipping requirements:

UN number 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibutyltin dilaurate)

Hazard class Packing 9 group Environmental III

hazards

Marine pollutant Yes EmS No. F-A, S-F

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Inventory name

Section 302 extremely hazardous substance (40 CRF 355, Appendix A)

No

Section 311/312 (40 CFR

Country(s) or region

No

370)

Inventory status

~ · · · · · · · · · · · · · · · · · · ·		(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

IdeaPaint CREATE part B (THIS)

On inventory (yes/no)*

Country(s) or region Inventory name On inventory (yes/no)*

New Zealand New Zealand Inventory No

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Dibutyltin dilaurate (CAS 77-58-7)

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2

Flammability: 0

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Issue date 10-05-2011

IdeaPaint CREATE part B (THIS)